

§ 1.136(a), and any fees required therefor (including fees for net addition of claims) are hereby authorized to be charged to our Deposit Account No. 19-0036.

Amendments

In the Claims:

Please substitute the following claims 1-14, 16, 19-32 and 34 for the pending claims 1-14, 16, 19-32 and 34:

1. (Amended) A method of conducting a wireless inventory of items using a network tag reader and tags, wherein a unique tag is attached to each item and each tag is permanently assigned a tag identification number (Tag ID), the method comprising the steps of:

a1 selecting one of a plurality of remote access sensor modules, which communicate wirelessly with the items, wherein the selected remote access sensor module comprises a coverage pattern that defines a physical area containing a plurality of items with their associated tags;

interrogating the tags in a defined physical area through the corresponding selected remote access sensor module, thereby receiving information from the tags in the defined physical area;

storing the information received in the interrogating step in an inventory database;

repeating the selecting, interrogating, and storing steps for each remote access sensor module; and

after the selecting, interrogating, and storing steps are performed for each remote access sensor module, processing the information in the inventory database.

2. (Amended) The method of claim 1, wherein the information received in the interrogating step comprises at least one Tag ID, each Tag ID corresponding to a tag within the physical area defined by the coverage pattern.

a1 3. (Amended) The method of claim 2, further comprising the step of repeating the selecting, interrogating, storing, repeating, and processing steps.

4. (Amended) The method of claim 3, wherein the storing step comprises the step of:
if a particular Tag ID received during an initial performance of the interrogating step has not been received during a subsequent performance of the interrogating step within a predetermined time period, storing information in the inventory database that indicates a tag corresponding to the particular Tag ID is missing.

5. (Amended) The method of claim 4, wherein the processing step comprises the step of initiating a security action when the particular Tag ID is missing.

6. (Amended) The method of claim 5, wherein the security action comprises turning on a surveillance camera.

7. (Amended) The method of claim 5, wherein the security action comprises activating a silent alarm.
8. (Amended) The method of claim 2, wherein the processing step comprises the step of correlating a remote access sensor module identity with each Tag ID received in the interrogating step to maintain data regarding the location of each tag corresponding to a Tag ID.
9. (Amended) The method of claim 1, wherein the information received in the interrogating step comprises sensor information originated by a sensor associated with a tag within the physical area defined by the coverage pattern.
10. (Amended) The method of claim 9, wherein the sensor information indicates tag movement and/or vibration.
11. (Amended) The method of claim 9, wherein the sensor information indicates ambient tag temperature.
12. (Amended) The method of claim 9, wherein the processing step comprises the step of analyzing the sensor information for a condition that indicates a security breach.
13. (Amended) The method of claim 12, wherein the condition that indicates a security breach comprises a temperature fluctuation.

a1
cont'd

14. (Amended) The method of claim 12, wherein the condition that indicates a security breach comprises a sudden vibration.

16. (Amended) The method of claim 1, wherein the interrogating step comprises the steps of:

at the network tag reader,

transmitting through the selected remote access sensor module a wake-up signal followed by a first clock signal;

at each tag within the physical area defined by the coverage pattern of the selected remote access sensor module,

incrementing a first tag count in response to the first clock signal, and

transmitting the Tag ID assigned to each tag when the Tag ID of each tag corresponds to the first tag count,

at the network tag reader,

incrementing a first reader count in response to the first clock signal,

storing a given first reader count when more than one tag responds to the first clock signal that corresponds to the given first reader count, and

transmitting through the selected remote access sensor module the given first reader count followed by a second clock signal; and

at each tag that responds to the transmitted given first reader count,

incrementing a second tag count in response to the second clock signal, and

transmitting a second number assigned to each tag when the second number of each tag corresponds to the second count.

ai
could

19. (Amended) A system for conducting a wireless inventory of items using a network tag reader and tags, wherein a unique tag is attached to each item and each tag is permanently assigned a tag identification number (Tag ID), the method comprising the steps of:

means for selecting one of a plurality of remote access sensor modules, which communicate wirelessly with the items, wherein the selected remote access sensor module comprises a coverage pattern that defines a physical area containing a plurality of items with their associated tags;

means for interrogating the tags in a defined physical area through the corresponding selected remote access sensor module, thereby receiving information from the tags in the defined physical area;

means for storing the information received by the interrogating means in inventory database;

means for repeating the selecting, interrogating, and storing means for each remote access sensor module; and

means for processing the information in the inventory database.

20. (Amended) The system of claim 19, wherein the information received by the interrogating means comprises at least one Tag ID, each Tag ID corresponding to a tag within the physical area defined by the coverage pattern.

21. (Amended) The system of claim 20, further comprising means for repeatedly invoking the selecting, interrogating, storing, repeating, and processing means.

AI
cont'd

22. (Amended) The system of claim 21, wherein the storing means comprises:

if a Tag ID received during an initial performance of the interrogating means has not been received during a subsequent performance of the interrogating means within a predetermined time period, means for storing information in the inventory database that indicates a tag corresponding to the Tag ID is missing.

23. (Amended) The system of claim 22, wherein the processing means comprises means for initiating a security action when a Tag ID is missing.

24. (Amended) The system of claim 23, wherein the means for initiating a security action comprises means for turning on a surveillance camera.

25. (Amended) The system of claim 23, wherein the means for initiating a security action comprises means for activating a silent alarm.

26. (Amended) The system of claim 20, wherein the processing means comprises means for correlating a remote access sensor module identity with each Tag ID received by the interrogating means to maintain data regarding the location of each tag corresponding to a Tag ID.

27. (Amended) The system of claim 19, wherein the information received by the interrogating means comprises sensor information originated by a sensor associated with a tag within the physical area defined by the coverage pattern.

a1
could

28. (Amended) The system of claim 27, wherein the sensor information indicates tag movement and/or vibration.

29. (Amended) The system of claim 27, wherein the sensor information indicates ambient tag temperature.

30. (Amended) The system of claim 27, wherein the processing means comprises means for analyzing the sensor information for a condition that indicates a security breach.

31. (Amended) The system of claim 30, wherein the condition that indicates a security breach comprises a temperature fluctuation.

32. (Amended) The system of claim 30, wherein the condition that indicates a security breach comprises a sudden vibration.

34. (Amended) The system of claim 19, wherein the means for interrogating comprises:
at the network tag reader,

means for transmitting through the selected remote access sensor module a wake-up signal followed by a first clock signal;

at each tag within the physical area defined by the coverage pattern of the selected remote access sensor module,

means for incrementing a first tag count in response to the first clock signal, and

21
cont'd

means for transmitting the Tag ID assigned to each tag when the Tag ID of each tag corresponds to the first tag count;

at the network tag reader,

means for incrementing a first reader count in response to the first clock signal,

means for storing a given first reader count when more than one tag responds to the first clock signal that corresponds to the given first reader count, and

means for transmitting through the selected remote access sensor module the given first reader count followed by a second clock signal; and

at each tag that responds to the transmitted given first reader count,

means for incrementing a second tag count in response to the second clock signal,

and

means for transmitting a second number assigned to each tag when the second number of each tag corresponds to the second count.

at
count

The following claims 37 and 38 have been added:

37. (New) The method of claim 1, further including the step of performing multiple reads of the tags by the network tag reader to avoid time slot contention, wherein the tag identification number includes a plurality of bits, wherein the tag reader uses a first plurality of the plurality of bits during a first read and a second plurality of the plurality of bits during a second read.

at
bits

38. (New) The system of claim 19, wherein the network tag reader performs multiple reads of the tags to avoid time slot contention, wherein the tag identification number includes a plurality of bits, wherein the tag reader uses a first plurality of the plurality of bits during a first read and a second plurality of the plurality of bits during a second read.

as
cont'd